



WONDER MAKERS  
ENVIRONMENTAL

# Containment Area Pressure Monitor

Product #51

Provides an easy assessment of the pressure differential between the inside and outside of an enclosure



- ▶ Meets OSH requirements for Class 1 work.
- ▶ Measures pressure differential in increments of 0.005 inches of water, effective to a maximum pressure of 15 PSIG (100kPa) and at a maximum temperature of 140° F (60° C).
- ▶ Built-in bubble level indicates vertical positioning; includes an L-bracket for mounting on the wall or a level surface.
- ▶ Complete instructions and sample documentation form included.

## Specifications

### Includes:

Magnehelic gauge with built-in bubble level, 20' of clear 3/4" flexible tubing, barb connection ports, calibration screwdriver, L-bracket, and carrying case

### Dimensions:

4-1/2" L x 5-1/2" W x 2-1/4" H

### Materials:

Aluminum, glass, and brass

### Weight:

3 lbs. 8 oz. (including case, L-bracket, and tubing)

### Finish:

Brushed aluminum

P.O. Box 50209, Kalamazoo, MI 49005-0209 • 2117 Lane Blvd, Kalamazoo, MI 49001

Phone: (888) 382-4154 • Fax: 269-382-4161

Visit our website: [www.wondermakers.com](http://www.wondermakers.com) • Mold Sensitized website: [www.moldsensitized.net](http://www.moldsensitized.net)